



**McCloskey  
Environmental**



# F-80R

## TRACKED RADIAL FEEDER STACKER

The EF-80R comprises of a large feeder hopper that transfers material onto an 80ft conveyor, all fitted to a slew ring assembly allowing for full 360° radial.

Designed to allow operators to stockpile/transfer material it eliminates double handling of materials. Its maneuverability makes this unit very versatile and makes it ideal for barge loading and unloading, rail loading / unloading and stockpiling, the ability to move parallel enables the operator to maneuver the unit parallel to the vessel meaning the machine can crab alongside.

The unit can also be compacted for transport on one low loader for easy site to site transport.

## FEATURES

- Hydraulic folding head section for transport minimizing setup time
- Hydraulically adjustable discharge height up to 10m
- Fuel efficient hydraulics system
- 4m tracks for superior maneuverability & stability
- User friendly hydraulic controls
- Dual hydraulic main drive system
- Remote near stabilizing legs for easy operator use
- Remote radio tracking
- Hopper extensions increasing capacity



# McCloskey Environmental

## LARGE FEEDER

- Steel hopper allows operators to load 13m<sup>3</sup> of standard aggregates with hopper extensions option to increase capacity.

## INTUITIVE CONTROL PANEL

- Easy to use control panel makes operating the machine simple.

## 80" MAIN CONVEYOR

- Heavy duty main 48" wide conveyor and 80' long offers hydraulic folding.

## HYDRAULIC FOLDING CONVEYOR

- Straight forward hydraulic controls to fold and unfold, raise and lower conveyor for easy transport.

## TRACKED MOBILITY

- Fully portable tracked unit with 4m wide tracks, allowing for maximum on-site stability.



## DIMENSIONS AND CAPACITIES

\* Engine specifications vary. Check with your dealer.

ENGINE	CAT 3.6 - 100KW (136HP) - STAGE V TIER 4 FINAL - 800TPH*	OVERHANG TRANSPORT	7.2M	STOCKPILE HEIGHT	10M (32' 10")
TRANSPORT HEIGHT	3.4M (11' 1")	WEIGHT	27,500KG APPROX. (60,627 LBS)	HOPPER CAPACITY	13M <sup>3</sup> (17 YD <sup>3</sup> )
TRANSPORT LENGTH	19.4M (63' 6")	WORKING MAX LENGTH	6.2M	PRODUCTION RATE (MAX)	800 TPH
		WORKING MAX HEIGHT	10M	RADIAL	FULL 360°

© Copyright 2021 McCloskey Environmental. All rights reserved. McCloskey is a trademark of McCloskey International.

McCloskey Environmental reserves the right to make changes to the information and design of the machines on this brochure without reservation and notification to the users. Information at time of print considered accurate – McCloskey Environmental assumes no liability resulting from errors or omissions in this document.